

Pocket Design Machine TS-326G-PD



TS-326G-PD



Advantages

30Cf qr v'ewqo c'le'r t'gulpi . 'hggf lpi 'cpf 'eqp'v'p'w'w'u'gy lpi 'v'uko r r'kh' 'y q'tn'kpi 'r t'qegf w't'gu0
 40Gs w'r r gf 'y kj 'hgh'/'cpf 'tki j v'qr g'tc'v'q'p'k'p'v'g't'h'c'eg. 'q'p'g'y q'tn'g't'ecp'o c'pci g'y q'o c'ej k'p'gu'cv'
 vj g'uco g'v'ko g0
 50Rt'q'h'g'u'k'p'cm' 'f' g'uki p'gf 'h'q't' 'l'g'c'p'u'r q'eng'v'u'q' 'h'p'k'uj 'f' g'r'k'ec'v'g'f' g'e'q't'c'v'k'g' 'u'gy lpi 'r' g'h'g'e'v'v'0
 60T'lej 'u'gy lpi 'r' c'w'g't'p'u'o c'n'g' 'l'g'c'p'u'r q'eng'v'u'o q't'g' 'd'g'c'w'k'h'w'f'c'p'f 'h'c'uj k'q'p'c'd'ng' 'l'p' 'c'r' r' g'c't'c'p'eg0
 70R't'q'f' w'eg' 'v'k'f' { 'c'p'f 'g'x'g'p' 'u'k'ej' g'u. 'g'h'g'e'v'k'g'v' 'l'o r' t'q'x'g' 'y' g' 'q'x'g't'c'm'i c't'o g'p'v'o c'n'k'p'i 's' w'c'k'v'0
 80T'w'p' 'u'g'c'f' k'q' 'h'q't' 'h'q'p'i 'j' q'w't'u. 'h'm'm' 'o' g'g'v' 'h'c't'i g' 'u'ec'g' 'o' c'u'u'r' t'q'f' w'e'v'k'q'p' 'f' g'o c'p'f' u0

Product Specifications:

Max sewing speed	2800rpm
Working air pressure	0.5Mpa
Length of stitching	0.8-12.8mm
Type of needle	DP*17

